



Coated Stock

CM-557

Collins Brand Inks for HP 45A Technology

Dark Image Fast Dry Time

CM-557 Coated Stock is a dye-based ink that produces a high quality image and dries well on gloss and matte coated substrates.

Ink Features

• Fluid base: Aqueous

• Colorant: Dye

• Flash Point: $> 100^{o}C$

• Shipping info: Non-Hazardous

Recommended Printer Settings

Pen driver voltage: 10.2 VFire pulse length: $2.2 \mu \text{s}$ Pulse warming: $40^{\circ}C$

Printhead Performance

 $\begin{array}{ll} \mbox{Decap time:} & < 1 \mbox{ min} \\ \mbox{Shelf life (single/bulk)} & 1 \mbox{ yr/6 mo} \end{array}$

Not recommended for bulk use

Cartridge Maintenance & Handling

- Use a water dampened lint-free cloth to clean the print head
- Wipe slowly and lightly across tip of the long edge with the print head facing down
- Forcing the wipe (too much pressure) may scratch the print head
- Use of a cloth with lint may clog the nozzles

Cartridge Storage

• Operating conditions: $10 - 40^{\circ}C$

• Storage conditions: $10 - 30^{\circ}C$

• Less than 1 day down: leave cartridges in the machine and wipe/purge before next use

 More than 1 day down: remove cartridges from machine and place cartridge clip (available from Collins Ink) over the head, wipe and purge before use

Rating: 1-5 (5=Best)

Substrate Performance • 600x300 DPI • Dryer: OFF

Disclaimer: The information presented in this data sheet is intended only as a guide and does not infer a warranty of performance. Results may vary depending upon many variables including the specific grade of substrate, environmental conditions, print speed, etc.

Sample Substrate	Copy Paper	70# Gloss	Matte	Chipboard	Clay Coat Box
Optical Density	.99	1.22	1.67	1.08	1.01
Unassisted Dry Time	1 sec	5 sec	2 sec	1 sec	1 sec
Wet Rub Adhesion	4	4	4	4	4